




8		7	
INDUCTANCE		LOSSES	WEIGHT
35 mH		3 Watts	1 Lbs

ECO No	DESCRIPTION	REV BY	DATE
M10673	UPDATED TO NEW SOLIDWORKS FORMAT.	EH	08/15/18




TOP VIEW

WIRE RANGE: 22-14 AWG
CAUTION-TERMINAL SCREW TIGHTENING
TORQUE: 4.50 in-lb MAX.



FRONT VIEW



RIGHT VIEW

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2			MATERIAL		CONFIDENTIAL AND PROPRIETARY INFORMATION THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION		
CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION					DESCRIPTION		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE: ANGLES: $\pm 1^\circ$ 1 PLACE .X: $\pm .1$ [2.5] 2 PLACE .XX: $\pm .03$ [0.76] 3 PLACE .XXX: $\pm .010$ [0.254]			DRAWN EH	DATE 08/15/18	DC LINK CHOKE (IA 35.00 mH)		
			CHECKED EH	DATE 08/15/18			
			APPROVED JG	DATE 09/17/18			
					SIZE D	DWG No. CD 1RB001	REV 05
					SCALE 3:1		SHEET 1 OF 1



N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455-4683
262.253.8200