INDUCTANCE	LOSSES	APPROX. WEIGHT (LBS)
0.4 mH	75 Watts	65

ECO No	DESCRIPTION	REV BY	DATE
M12182	UPDATED OVERALL WIDTH DIMENSION	EH	02/13/20



TOP VIEW



BOTTOM VIEW





FRONT VIEW



SIDE VIEW

NOTES:

1. TERMINAL WIRE RANGE: 0000-2 AWG.
2. TERMINAL SCREW TIGHTENING TORQUE: 150 IN\LBS.
3. REFER TO USER MANUAL FOR COMPLETE INSTALLATION INSTRUCTIONS.

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2

CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:

ANGLES: ± 1 °

1 PLACE .X: ± .1 [2.5]

2 PLACE .XX: ± .03 [0.76]

3 PLACE .XXX: ± .010 [0.254]

MTE
POWER QUALITY. SOLVED.

N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455-4683
262.253.8200

MATERIAL

DRAWN	DATE
BET	08/28/96
CHECKED	DATE
EH	02/13/20
APPROVED	DATE
AK	02/19/20

CONFIDENTIAL AND PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION

DESCRIPTION

DC LINK CHOKE (200A 0.40m H)

SIZE	DWG No.	REV
D	CD 200RB003	08

SCALE 2:3 SHEET 1 OF 1