| WEIGHT (LBS) | INDUCTANCE | LOSS (WATTS) |
|---|---|---|
| 4 | 1.375 mH | 9 |

| ECO No | DESCRIPTION | REV BY | DATE |
|---|---|---|---|
| M12797 | CHANGE SCREW-5 FOR SCREW-146 AND UPDATE TITLEBLOCK | WF | 03/27/20 |













NOTES:
1. TERMINAL SCREW TORQUE 16 IN-LBS
2. WIRE RANGE 18-4 AWG

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2

CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:

ANGLES: ± 1 °

1 PLACE .X: ± .1 [2.5]

2 PLACE .XX: ± .03 [0.76]

3 PLACE .XXX: ± .010 [0.254]

MTE
POWER QUALITY. SOLVED.
N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455-4683
262.253.8200

MATERIAL

| | | | |
|---|---|---|---|
| DRAWN | AGK | DATE | 6/28/05 |
| CHECKED | WF | DATE | 03/27/20 |
| APPROVED | AK | DATE | 03/27/20 |

CONFIDENTIAL AND PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION

DESCRIPTION

DC CHOKE

| SIZE | DWG No. | REV |
|---|---|---|
| B | CD DCA001802 | 04 |

SCALE 1:2 SHEET 1 OF 1