WEIGHT (LBS)	INDUCTANCE	LOSS (WATTS)
13	6 mH	20

ECO No	DESCRIPTION	REV BY	DATE
M12797	CHANGE SCREW-5 FOR SCREW-146 AND UPDATE TITLEBLOCK	WF	03/27/20





VIEW A-A





NOTES:
1. TERMINAL SCREW TORQUE 16 IN-LBS
2. WIRE RANGE 18-4 AWG

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2

CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:

ANGLES: ± 1 °

1 PLACE .X: ± .1 [2.5]

2 PLACE .XX: ± .03 [0.76]

3 PLACE .XXX: ± .010 [0.254]

MTE
POWER QUALITY. SOLVED.
N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455-4683
262.253.8200

MATERIAL

DRAWN	AGK	DATE	6/28/05
CHECKED	WF	DATE	03/27/20
APPROVED	AK	DATE	03/27/20

CONFIDENTIAL AND PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION

DESCRIPTION

DC CHOKE

SIZE	DWG No.	REV
B	CD DCA001805	04

SCALE 1:2 SHEET 1 OF 1