



APPROX. WEIGHT
(LBS)
9

ECO No	DESCRIPTION	REV BY	DATE
M11950	UPDATED TO LATEST STANDARD	WF	02/20/20




TOP VIEW

SEE NOTE 1




BOTTOM VIEW




FRONT VIEW

SEE NOTE 2



SIDE VIEW



NOTES:

1. TERMINAL WIRE RANGE: 6-0 AWG.
2. TERMINAL SCREW TIGHTENING TORQUE: 6-4 (45 IN•LBS), 2-0 (50 IN•LBS).
3. REFER TO USER MANUAL FOR COMPLETE INSTALLATION INSTRUCTIONS.

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2		MATERIAL		CONFIDENTIAL AND PROPRIETARY INFORMATION THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION	
CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION				DESCRIPTION	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE: ANGLES: ± 1 ° 1 PLACE .X: ± .1 [2.5] 2 PLACE .XX: ± .03 [0.76] 3 PLACE .XXX: ± .010 [0.254]		MTE POWER QUALITY. SOLVED. N83 W13330 Leon Road Menomonee Falls, WI 53051 USA 800.455-4683 262.253.8200		DC LINK CHOKE (92A 0.20mH)	
		DRAWN AGK	DATE 06/28/05	SIZE D	DWG No. CD DCA009201
		CHECKED WF	DATE 02/20/20	REV 04	
		APPROVED AK	DATE 02/24/20	SCALE 1:1	SHEET 1 OF 1