APPROX. WEIGHT (LBS)
174

ECO No	DESCRIPTION	REV BY	DATE



TOP VIEW



BOTTOM VIEW



DETAIL B
(6 PLACES)





DETAIL A
(2 PLACES)



DETAIL E
CUSTOMER CONNECTION
(THERMAL)



DETAIL D
(3 PLACES)



CUSTOMER CONNECTION
DETAIL VIEW



FRONT VIEW



SIDE VIEW

NOTES:

1. **FILTER REQUIRES CAP-376TP (QTY. 2)**
2. **TERMINAL SCREW TIGHTENING TORQUE: 16 IN/LBS**
3. **WIRE RANGE: 4-14 AWG.**

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2

CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:

ANGLES: ± 1 °

1 PLACE .X: ± .1 [2.5]

2 PLACE .XX: ± .03 [0.76]

3 PLACE .XXX: ± .010 [0.254]

MTE
POWER QUALITY. SOLVED.

N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455-4683
262.253.8200

MATERIAL

DRAWN: KV	DATE: 04/20/18
CHECKED: KV	DATE: 10/09/18
APPROVED: JG	DATE: 10/11/18

CONFIDENTIAL AND PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION

DESCRIPTION

MATRIX AP 208A 240V 60Hz
OPEN PANEL

SIZE	DWG No.	REV
D	CD MAPP0208A	00

SCALE 1:3 SHEET 1 OF 1