APPROX. WEIGHT (LBS)
225

ECO No	DESCRIPTION	REV BY	DATE



TOP VIEW



BOTTOM VIEW



DETAIL E
CUSTOMER CONNECTION
DETAIL VIEW (THERMAL)



DETAIL C
(6 PLACES)



DETAIL B
(3 PLACES)



DETAIL A
(2 PLACES)



FRONT VIEW



SIDE VIEW



CUSTOMER CONNECTION
DETAIL VIEW

NOTES:

1. **FILTER INCLUDES CAPPANEL-153 (QTY. 1).**
2. **TERMINAL SCREW TIGHTENING TORQUE: 16 IN/LBS**
3. **WIRE RANGE: 4-14 AWG.**

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2

CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:

ANGLES: ± 1 °

1 PLACE .X: ± .1 [2.5]

2 PLACE .XX: ± .03 [0.76]

3 PLACE .XXX: ± .010 [0.254]

MTE POWER QUALITY. SOLVED.

N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455-4683
262.253.8200

MATERIAL

DRAWN	KV	DATE 09/04/18
CHECKED	KV	DATE 09/04/18
APPROVED	AK	DATE 10/03/18

CONFIDENTIAL AND PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION

DESCRIPTION

MATRIX AP 240A 240V 60Hz
OPEN PANEL

SIZE	DWG No.	REV
D	CD MAPP0240A	00

SCALE 1:3 SHEET 1 OF 1