



APPROX WEIGHT  
(LBS.)  
19

ECO No	DESCRIPTION	REV BY	DATE
M9684	CHANGE LEAD-027 TO -327 & -028 TO -328	MN	10/09/15



NOTE:  
1. TIGHTEN STANDOFF SCREWS TO 58 IN/LBS. TORQUE, MAX.

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2		MATERIAL		CONFIDENTIAL AND PROPRIETARY INFORMATION THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION			
CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION				DESCRIPTION			
<div>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:  ANGLES: ± 1 °  1 PLACE .X: ± .1 [2.5]  2 PLACE .XX: ± .03 [0.76]  3 PLACE .XXX: ± .010 [0.254]</div>		<div>  N83 W13330 Leon Road Menomonee Falls, WI 53051 USA 800.455.4683 262.253.8200</div>		3 CAP ASSEMBLY 300uF CAB-26AP MATRIX SINGLE PHASE			
		DRAWN	DATE	SIZE	DWG No.	REV	
		MM	03/20/15				
		CHECKED	DATE	SCALE	2:3	SHEET 1 OF 1	
		TM	10/13/15				
		APPROVED	DATE				
		TM	10/13/15				