WEIGHT (LBS)	INDUCTANCE	LOSS (WATTS)
28	2.12mH	204

ECO No	DESCRIPTION	REV BY	DATE
M9376	UPDATE GRAPHICS AND CORRECT WEIGHT	MN	11/11/14







VIEW A-A



NOTES:

1. TERMINAL SCREW TIGHTENING TORQUE:
   - 16 in-lbs MAX
2. WIRE RANGE: 14 - 6 AWG

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS

CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:

ANGLES: ± 1 °

1 PLACE .X: ± .1 [2.5]

2 PLACE .XX: ± .03 [0.76]

3 PLACE .XXX: ± .010 [0.254]

MTE
AN SL POWER ELECTRONICS COMPANY

N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455.4683
262.253.8200

MATERIAL

DRAWN: JP	DATE: 09/26/12
CHECKED: RH	DATE: 11/11/14
APPROVED: RH	DATE: 11/11/14

CONFIDENTIAL AND PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION

DESCRIPTION

3 PHASE REACTOR

SIZE	DWG No.	REV
D	CD RLW-003507	02

SCALE 1:1 — SHEET 1 OF 1