APPROX. WEIGHT (LBS)
962

ECO No	DESCRIPTION	REV BY	DATE



FRONT VIEW
(PANELS REMOVED)



LUG VIEW
(6 PLACES)



SIDE VIEW



DETAIL B
CUSTOMER CONNECTION
DETAIL VIEW (THERMAL)





BOTTOM VIEW



TOP VIEW
(PANELS REMOVED)



(CAPPANEL REMOVED)



CUSTOMER CONNECTION
DETAIL VIEW

NOTES:

1. TIGHTEN TERMINAL BLOCK SCREWS TO 16 IN/LBS. TORQUE.
2. TERMINAL WIRE SIZE: 4-14 AWG.

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2

CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:

ANGLES: ± 1 °

1 PLACE .X: ± .1 [2.5]

2 PLACE .XX: ± .03 [0.76]

3 PLACE .XXX: ± .010 [0.254]

MTE POWER QUALITY. SOLVED.

N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455.4683
262.253.8200

MATERIAL

DRAWN	DATE
MN	08/28/18
CHECKED	DATE
MN	09/14/18
APPROVED	DATE
TL	10/09/18

CONFIDENTIAL AND PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION

DESCRIPTION

SWG 515A 600V 2-8kHz
FILTER, NEMA 3R ENCL.

SIZE	DWG No.	REV
D	CD SWGW0515E	00

SCALE 1:8 SHEET 1 OF 1